

Product and technical data sheet

Green Blade[®] veneered panels

Substrate	MDF	Particle board
Dimensions (mm)	1210 x 2420	1210 x 2480
Thickness (mm)	16 / 18 , other upon request	
One sided / Double sided	A/A or A/C	
Finish	Yes - (pre-finish primer upon request)	
Type of finish	Extra Matte to Ultra Gloss	
Waterproof	Upon request	
Fire rated	Upon request	
Certification	FSC	

Product and technical data sheet

Green Blade[®] edge banding

Visible edges should always be covered for a clean finish, and an effective protection. FIBANDCO now offers quality Green Blade[®] edge banding, for all types of panels.

Application for Green Blade[®] edge banding

The edge banding is not pre glued and is to be used on an edge bander with hot melt adhesives, then applied to the substrate. The temperature of the adhesive is approximately 210 °C. The thick edge banding can also be applied with white glue and manual tightening.

To achieve high quality bonding, all of your components must have a homogeneous temperature. Storage of the substrates and edge banding protected from the weather, moisture, but also heat, ensures application without problems.

Characteristics

	Green Blade[®] Edge banding
Length (m)	By the meter
Width (mm)	22 or upon request
Thickness (mm)	1
Pre glued	No
Finish	Upon request